



## Model ACen Duo wallbox 22

**Ideal for hybrids & electrics, at home, at work, hotels, parking lots ...**

### Properties

- » ACen Duo: maximum 22kW per channel
- » Single-phase or 3-phase connection
- » 2 sockets
- » 2 power connections (max 32A)
- » Integrated DC leakage current detection 30mA AC / 6mA DC

### Why choosing a CenEnergy charging station?

- » Start / stop with RFID
- » Online management
- » Helpdesk 24/7
- » Billing and split billing
- » Powder-coated aluminum housing
- » Corrosion and scratch resistant



#### Headquarters

Boomsesteenweg 12 – unit 8  
2630 Aartselaar

Tel.: +32 3 334 07 06

[info@cenenergy.be](mailto:info@cenenergy.be)

[www.cenenergy.be](http://www.cenenergy.be)



## Model ACen Duo wallbox 22 – technical information

### Charging

- » Vehicle interface: 2x Type 2 socket
- » Power rating: 1P+N (230V AC @ 32A // 7.5kW per channel
- » Power rating: 3P + N (3x 230V AC @ 32A // 22kW per channel

### Operating conditions

- » IP54: indoor/outdoor
- » Operating temperature: -25°C to 55°C
- » Standby Power: 1.2W

### Mechanicals

- » 3mm aluminum casing
- » Powder coating
- » 657 mm x 310 mm x 186 mm

### Technical drawing

